



APPENDIX A CONSTRUCTION PROGRAMME AND PROACTIVE ENVIRONMENTAL PROTECTION PROFORMA

Construction Programme (Apr 2024 – Jun 2025)











Layout Plan with major construction activities





Proactive Environmental Protection Proforma

Design and Construction of Kong Nga Po Police Training Facilities <u>Proactive Environmental Protection Proforma</u>

Working	Period	: Apr to	Jun	2025
---------	--------	----------	-----	------

Ref*	Proposed	Location/Working	Anticipated Major	Recommended Mitigation Measures
	Construction	Period	Impacts	
	Method			
EIA 3.9.1; EM&A Log 2.2	Open cut excavation	Kong Nga Po Site	Dust impact from excavation activities and earth moving	times per day) at all active works area exposed site surfaces
				wheel of all vehicles before leaving the site
EIA 4.4.6;			Noise Control	Regular inspection and maintenance of plant & equipment in
EM&A Log 3.2				good condition

EIA 5.6.1.2; EM&A Log 4.2	Working in Restricted Hours Water Pollution Control	 Enclose the noisy part of machineries with noise enclosure Adopt of Quality Powered Mechanical Equipment (QPME) if possible Valid construction noise permit should be obtained and displayed on site In case of non-compliance with the construction noise criteria, more frequent monitoring and action should be carried out Cover the stockpiles of construction materials to reduce the potential for water pollution Provide wastewater treatment facilities prior to discharge of wastewater Regular inspection and maintenance of wastewater treatment facilities Wastewater pumped out of the excavation areas will be treated to remove suspended solids prior to discharge Hard paving or well-compact of main haul road to minimize washout of soil Wheels of all vehicles and plants will be cleaned before leaving the work areas to remove sediment, soil and debris from the tracked. The wastewater will be treated and reused on site or discharged.
EIA 7.5.1.1 &	Waste Generation	Training of site personnel in proper waste management and

7.5.1.2;				chemical handling procedures
EM&A Log 6.2				Proper storage and sorting of excavated inert materials to
				maximize on site reuse for backfilling
				Surplus inert C&D materials will be disposed of at designated
				Government's PFRF.
EIA 7.5.1.4;			Chemical Waste	Chemical waste should be stored at chemical waste container
EM&A Log 6.2				and collected by a licensed collector to transport and dispose
				of at the approved Chemical Waste Treatment Centre
				Drip tray and chemical spillage kit will be provided on site
EIA 9.7.1 and			Ecology Concern	Provide training to frontline workers for the conservative
EM&A Log 8.3				species
				Provision of protective fence for the conservative species
				Regular inspection for concerned vegetation and conservative
				species
EIA Table 10.11;			Landscape and	Preservation of existing trees will be undertaken in
EM&A Table 9.1			Visual Impact	accordance with DEVB TC(W) 7/2015 and Guidelines for Tree
				Risk Assessment and Management Arrangement
				Restrict construction area to minimize the impact on existing
				retained trees
EIA 3.9.1;	Soil Removal	Kong Nga Po Site	Dust impact from	Use of regular water spraying (once every 1.25 hours or 8
EM&A Log 2.2			excavation	times per day) at all active works area exposed site surfaces
			activities and earth	and unpaved roads, particularly during dry weather

EIA 4.4.6; EM&A Log 3.2	Noise Control	 Water spraying during loading and unloading of excavated materials Vehicles used for transporting dusty materials/spoils will be covered by mechanical cover before leaving the site Deploy water bowser for regular water spraying to enhance dust suppression Speed control of site transportation Stockpile of dusty materials will be covered by tarpaulin sheets to avoid wind-blown dust Wheel washing facilities will be provided and cleaning the wheel of all vehicles before leaving the site Regular inspection and maintenance of plant & equipment in good condition Enclose the noisy part of machineries with noise enclosure
		Adopt of Quality Powered Mechanical Equipment (QPME) if possible
	Working in	Valid construction noise permit should be obtained and
	Restricted Hours	displayed on site
		In case of non-compliance with the construction noise criteria,
		more frequent monitoring and action should be carried out
EIA 5.6.1.2;	Water Pollution	Cover the stockpiles of excavated materials to reduce the
EM&A Log 4.2	Control	potential for water pollution

EIA 7.5.1.1 & 7.5.1.2; EM&A Log 6.2	Waste Generation	 Provide wastewater treatment facilities prior to discharge of wastewater Regular inspection and maintenance of wastewater treatment facilities Wheels of all vehicles and plants will be cleaned before leaving the work areas to remove sediment, soil and debris from the tracked. The wastewater will be treated and reused on site or discharged. Training of site personnel in proper waste management and chemical handling procedures Proper storage and sorting of excavated inert materials to maximize on site reuse for backfilling
		 Surplus inert C&D materials will be disposed of at designated Government's PFRF.
EIA 7.5.1.4; EM&A Log 6.2	Chemical Waste	 Chemical waste should be stored at chemical waste container and collected by a licensed collector to transport and dispose of at the approved Chemical Waste Treatment Centre Drip tray and chemical spillage kit will be provided on site
EIA 9.7.1 and EM&A Log 8.3	Ecology Concern	 Provide training to frontline workers for the conservative species Provision of protective fence for the conservative species Regular inspection for concerned vegetation and conservative

				species
EIA Table 10.11; EM&A Table 9.1			Landscape and Visual Impact	 Preservation of existing trees will be undertaken in accordance with DEVB TC(W) 7/2015 and Guidelines for Tree Risk Assessment and Management Arrangement Restrict construction area to minimize the impact on existing retained trees
EIA 3.9.1; EM&A Log 2.2	Construction of footings	Kong Nga Po Site	Air	 Regular inspection and maintenance of plant and equipment in good condition Regularly clean up stockpiles and debris to avoid accumulation of materials Dusty materials exceeding 20 bags shall be stored in area sheltered on top and the three sides or covered entirely by impervious sheeting.
EIA 4.4.6; EM&A Log 3.2			Noise Control	 Regular inspection and maintenance of plant & equipment in good condition Enclose the noisy part of machineries with noise enclosure Adopt of Quality Powered Mechanical Equipment (QPME) if possible
			Working in Restricted Hours	 Valid construction noise permit should be obtained and displayed on site In case of non-compliance with the construction noise criteria, more frequent monitoring and action should be carried out

EIA 5.6.1.2;			Water Pollution	Wheels of all vehicles and plants will be cleaned before
EM&A Log 4.2			Control	leaving the work areas to remove sediment, soil and debris
				from the tracked. The wastewater will be treated and reused
				on site or discharged.
				Designated location for residual concrete washout
				Provide wastewater treatment facilities prior to discharge of
				wastewater
EIA 7.5.1.4;			Chemical Waste	Drip tray and chemical spillage kit shall be provided on site
EM&A Log				
EIA 9.7.1 and			Ecology Concern	Provide training to frontline workers for the conservative
EM&A Log 8.3				species
				Provision of protective fence for the conservative species
				Regular inspection for concerned vegetation and conservative
				species
EIA Table 10.11;			Landscape and	Preservation of existing trees will be undertaken in
EM&A Table 9.1			Visual Impact	accordance with DEVB TC(W) 7/2015 and Guidelines for Tree
				Risk Assessment and Management Arrangement
				Implement temporary traffic arrangement which control
				construction area to minimize landscape and visual impacts
EIA 3.9.1;	Construction	Kong Nga Po Site	Air	Regular inspection and maintenance of plant and equipment
EM&A Log 2.2	of substructure			in good condition
	and			Regularly clean up stockpiles and debris to avoid

	superstructure		 accumulation of materials Dusty materials exceeding 20 bags shall be stored in area sheltered on top and the three sides or covered entirely by impervious sheeting.
EIA 4.4.6; EM&A Log 3.2		Noise Control	 Regular inspection and maintenance of plant & equipment in good condition Enclose the noisy part of machineries with noise enclosure Adopt of Quality Powered Mechanical Equipment (QPME) if possible
		Working in Restricted Hours	 Valid construction noise permit should be obtained and displayed on site In case of non-compliance with the construction noise criteria, more frequent monitoring and action should be carried out
EIA 5.6.1.2; EM&A Log 4.2		Water Pollution Control	 Cover the stockpiles of construction materials to reduce the potential for water pollution Provide wastewater treatment facilities prior to discharge of wastewater Wastewater generated from surface runoff shall be treated prior to discharge Manholes should be temporarily sealed to prevent silt, construction materials or debris from entering the drainage system.

EIA 7.5.1.1; EM&A Log 6.2			Waste Management	 Cover stockpiles of C&D materials by impervious sheets to avoid wind-blown dust. Spray water on all dusty materials including C&D materials immediately prior to any loading transfer operation Segregation and storage of different types of waste in different containers or skips to enhance reuse or recycling of materials and their proper disposal
EIA 7.5.1.4; EM&A Log 6.2			Chemical Waste	Drip tray and chemical spillage kit shall be provided on site
EIA 9.7.1 and EM&A Log 8.3			Ecology Concern	 Provide training to frontline workers for the conservative species Provision of protective fence for the conservative species Regular inspection for concerned vegetation and conservative species
EIA Table 10.11;			Landscape and	• Preservation of existing trees will be undertaken in
EM&A Table 9.1			Visual Impact	 accordance with DEVB TC(W) 7/2015 and Guidelines for Tree Risk Assessment and Management Arrangement Implement temporary traffic arrangement which control construction area to minimize landscape and visual impacts
EIA 3.9.1;	Construction	Kong Nga Po Site	Air	Regular inspection and maintenance of plant and equipment
EM&A Log 2.2	of footbridge			in good condition

		 Water spraying during loading and unloading of excavated materials Regularly clean up stockpiles and debris to avoid accumulation of materials Dusty materials exceeding 20 bags shall be stored in area sheltered on top and the three sides or covered entirely by impervious sheeting.
EIA 4.4.6;	Noise Control	Regular inspection and maintenance of plant & equipment in
EM&A Log 3.2		good condition
		 Adopt of Quality Powered Mechanical Equipment (QPME) if possible
	Working in	Valid construction noise permit should be obtained and
	Restricted Hours	displayed on site
		In case of non-compliance with the construction noise criteria,
		more frequent monitoring and action should be carried out
EIA 5.6.1.2;	Water Pollution	Cover the stockpiles of construction materials to reduce the
EM&A Log 4.2	Control	potential for water pollution
		Provide wastewater treatment facilities prior to discharge of
		wastewater
		Wastewater generated from surface runoff shall be treated
		prior to discharge
EIA 7.5.1.1;	Waste	Cover stockpiles of C&D materials by impervious sheets to

EM&A Log 6.2			Management	 avoid wind-blown dust. Spray water on all dusty materials including C&D materials immediately prior to any loading transfer operation Segregation and storage of different types of waste in different containers or skips to enhance reuse or recycling of materials and their proper disposal
EIA 7.5.1.4; EM&A Log 6.2			Chemical Waste	Drip tray and chemical spillage kit shall be provided on site
EIA Table 10.11; EM&A Table 9.1			Landscape and Visual Impact	 Preservation of existing trees will be undertaken in accordance with DEVB TC(W) 7/2015 and Guidelines for Tree Risk Assessment and Management Arrangement Implement temporary traffic arrangement which control construction area to minimize landscape and visual impacts
EIA 3.9.1; EM&A Log 2.2	Backfilling	Kong Nga Po Site	Air	 Deploy water bowser for regular water spraying to enhance dust suppression Manual water spraying for dusty operation where inaccessible by water bowser Speed control of site transportation Stockpile of dusty materials will be covered by tarpaulin sheets to avoid wind-blown dust Vehicles used for transporting dusty materials/spoils will be covered by mechanical cover before leaving the site

		Wheel washing facilities will be provided and cleaning the wheel of all vehicles before leaving the site
EIA 4.4.6; EM&A Log 3.2	Noise Control	 Regular inspection and maintenance of plant & equipment in good condition Enclose the noisy part of machineries with noise enclosure
		 Adopt of Quality Powered Mechanical Equipment (QPME) if possible
	Working in Restricted Hours	Valid construction noise permit should be obtained and displayed on site
		 In case of non-compliance with the construction noise criteria, more frequent monitoring and action should be carried out
EIA 5.6.1.2;	Water Pollution	Cover the stockpiles of construction materials to reduce the
EM&A Log 4.2	Control	potential for water pollution
		 Provide wastewater treatment facilities prior to discharge of wastewater
		Regular inspection and maintenance of wastewater treatment facilities
		Wastewater pumped out of the excavation areas will be
		treated to remove suspended solids prior to discharge
		Hard paving or well-compact of main haul road to minimize
		washout of soil
		Wheels of all vehicles and plants will be cleaned before

		leaving the work areas to remove sediment, soil and debris from the tracked. The wastewater will be treated and reused on site or discharged.
EIA 7.5.1.1 &	Waste Generation	Training of site personnel in proper waste management and
7.5.1.2;		chemical handling procedures
EM&A Log 6.2		Proper storage and sorting of excavated inert materials to
		maximize on site reuse for backfilling
		Surplus inert C&D materials will be disposed of at designated
		Government's PFRF or reuse at other contracts.

^{*}EIA Ref/EM&A Log/ Design Document Ref

^{**}Details of equipment, vehicles, plants, processes, technologies for the construction method

Design and Construction of Kong Nga Po Police Training Facilities <u>Proactive Environmental Protection Proforma</u>

Working Period: April 202	Working	Period:	April	2025
---------------------------	---------	---------	-------	------

Ref*	Proposed	Location/Working	Anticipated	Recommended Mitigation	Photo Records (Partial)
	Construction	Period	Major Impacts	Measures	
	Method				
EIA 3.9. EM&A Lo 2.2		Kong Nga Po Site	Dust impact	 Manual water spraying for dust suppression Regular inspection and maintenance of plant and equipment in good condition Cover stockpile with impervious sheets or 	2025
				grout	By subcontractor at KNP site
				Provide wheel washing	
				facility at site entrance	

	By subcontractor at KNP site 12.04.2025
	By subcontractor at KNP site

EIA 4.4.6;	Noise	Regular inspection and	
EM&A Log		maintenance of plant &	No. of the last of
3.2		equipment in good condition Deploy Quality Powered Mechanical Equipment (QPME) if possible Valid construction noise	KRIERNOISE BARRIERNOISE BARRIER (X2009 陽音器 CX2009 陽音器 CX2009 陽音器 CX2009 陽音器
		permit should be	By main contractor at KNP site
		displayed at site entrance.	CUBAC CUMPLE CUMPLE CONTROL CO

By main contractor at KNP site

EIA 9.7.1 and EM&A Log		Ecology Concern	•	Provide workers	training about	to the	
8.3			•	Provision fence	of protection for	ctive the	
			•	Regular	tive species inspection d vegeta	for	17.04
				and species	conserva	ative	By main contractor at KNP site
							By subcontractor at KNP site

EIA 3.9.1;	Soil Removal	Kong Nga Po Site	Air	•
EM&A Log				
2.2				
				•
				•
				•

- Deploy water bowser for regular water spraying to enhance dust suppression
- Cover dusty materials with impervious sheets
- Exposed slopes covered with waterproof layers such as tarpaulin sheets or grout to reduce the potential for sediment laden runoff entering the drainage system.
- The speed of the trucks within the site should be controlled to about 10km/hour in order to reduce adverse dust impacts and secure the safe movement around the site.



By main contractor at KNP site



By subcontractor at KNP site

EIA 4.4.6; EM&A Log 3.2	Noise	Regular inspection and maintenance of plant & equipment in good condition Deploy Quality Powered Mechanical Equipment (QPME) if possible By main contractor at KNP site
EIA 5.6.1.2 and EM&A Log 4.2	Water Quality	 Cover exposed slopes with impervious sheets or cement grout. Wastewater pumped out of the excavation areas shall be treated to remove suspended solid prior to discharge. Provide desilting/sedimentation devices for wastewater treatment prior to discharge.

Provide drip tray to
By main contractor at KNP site By main contractor at KNP site

EIA	Table	
10.11;		
EM&A	Table	
9.1		

Landscape and Visual Impact

- Preservation of existing trees will be undertaken in accordance with DEVB TC(W) 7/2015 and Guidelines for Tree Risk Assessment and Management Arrangement
- traffic arrangement which control construction area to minimize landscape and visual impacts
- Minimize visual impact during construction stage. Site office not visually prominent from public room and surrounding
- Planting will take place as soon the planting area is installed with



By main contractor at KNP site



By main contractor at KNP site

				subsoil drainage	
				 Decorative hoarding is 	
				provided	
EIA 3.9.1; EM&A Log 2.2	Construction of footings, substructure and superstructure	Kong Nga Po Site	Air	 Cover dusty materials with impervious sheets Exposed slopes covered with waterproof layers such as tarpaulin sheets or grout to reduce the potential for sediment laden runoff entering the drainage system. Provide wheel washing facility at site entrance 	10.04.2025 By main contractor at KNP site
					22.04.2025
					By subcontractor at KNP site

EIA 4.4.6; EM&A Log 3.2	Noise	Valid construction noise permit should be obtained and displayed on site	環境許可證 建築噪音許可證 construction Noise Permit O7.04.2025 By main contractor at KNP site
EIA 5.6.1.3 and EM&A Log 4.2	Water Quality	 Surface water from concrete batching areas and the rest of the site should be separated as far as possible. Temporary drainage is free of obstruction. Gullies are sealed to 	By subcontractor at KNP site

	By subcontractor at KNP site
	By subcontractor at KNP site

	By main contractor at KNP site
	By main contractor at KNP site

	By main contractor at KNP site
	By main contractor at KNP site

EIA 7.5.1.2	Waste	•	Segregation and storage	
and EM&A	Management		of different types of	
Log 6.2			waste in different	
			containers or skips or	非原性及和 (Americal Applie
			stockpiles to enhance	1175051441
			reuse or recycling of	
			materials and their	24.04.2025
			proper disposal	24.04.2025
		•	Sort non-inert C&D	By main contractor at KNP site
			materials to recover any	
			recyclable portions	